

BMW – Serie 4000 COM



VS-4000-C-BMW-INT-01

- 1 Combined 4-Gas-Tester and Diesel-Opacimeter, Printer integrated
- 1 Exhaust probe PU (Gas)
- 1 Opacity chamber 4000
- 1 Exhaust probe Diesel
- 1 Control cable 4000 6m
- 1 Cable-trigger 4000
- 1 Clamp-on transducer KG 60 + Cable 5m
- 1 User manual 4000
- RPM measurement via trigger cable or clamp-on transducer.
- 2MB Memory Adapter integrated

AECS Ltd



VS-DIX-250-TYP-INT-01

- Emission tester AVL DiGas 480
- AVKL DiLink 480
- Exhaust hose
- Emission sensor
- Catch for emission sensor
- PC
- Keyboard with protective film
- 15" TFT color monitor
- Laser printer
- Rpm measurement at ignition cable
- TN signal and acoustic via integral AVL DiSpeed 490
- Engine oil temperature sensor
- Mobile equipment trolley
- MB exhaust emissions inspection specifications
- Alternative DC method
- Operating instructions

AECS Ltd



VS-DIX-350-TYP-INT-01

- AVL DiSmoke 480
- AVL Di Link 480
- Emission sensor
- Control cable
- PC
- Keyboard with protective film
- 15" TFT color monitor
- Laser printer
- Rpm measurement acoustic and via TN signal
- Engine oil temperature sensor
- Mobile equipment trolley
- MB exhaust emissions inspection specifications
- Diesel emissions inspection OBD procedure as standart, including operating instructions



VS-DIX-450-TYP-INT-01

- Emission tester AVL DiGas 480
- AVL DiSmoke 480
- AVL DiLink 480
- Exhaust hose
- Emission sensor
- Catch for emission sensor
- PC
- Keyboard with protective film
- 15" TFT color monitor
- Laser printer
- Rpm measurement at ignition cable
- TN signal and acoustic via integral AVL DiSpeed 490
- Engine oil temperature sensor
- Mobile equipment trolley
- MB exhaust emissions inspection specifications
- Alternative DC method
- Diesel OBD emissions inspection procedure
- Operating instructions

AECS Ltd